

DHV TESTREPORT EN926-2:2014

MAC PARA EDEN 7 26

Type designation MAC Para Eden 7 26
Type test reference no DHV GS-01-2480-19
Holder of certification [MAC Para Technology](#)
Manufacturer [MAC Para Technology](#)
Classification B
Winch towing Yes
Number of seats min / max 1 / 1
Accelerator Yes
Trimmers No



BEHAVIOUR AT MIN WEIGHT IN FLIGHT (82KG)

BEHAVIOUR AT MAX WEIGHT IN FLIGHT (103KG)

Test pilots



Beni Stocker

No release



Harald Buntz

No release

Inflation/take-off

Rising behaviour Smooth, easy and constant rising
Special take off technique required No

Smooth, easy and constant rising
 No

Landing

Special landing technique required No

No

Speeds in straight flight

Trim speed more than 30 km/h Yes
Speed range using the controls larger than 10 km/h Yes
Minimum speed Less than 25 km/h

Yes
 Yes
 Less than 25 km/h

Control movement

Symmetric control pressure Increasing
Symmetric control travel Greater than 60 cm

Increasing
 Greater than 65 cm

Pitch stability exiting accelerated flight

Dive forward angle on exit Dive forward less than 30°
Collapse occurs No

Dive forward less than 30°
 No

Pitch stability operating controls during accelerated flight

Collapse occurs No

No

Roll stability and damping

Oscillations Reducing

Reducing

Stability in gentle spirals

Tendency to return to straight flight Spontaneous exit

Spontaneous exit

en : Verhalten beim Verlassen einer vollständigen Steilspirale

en : Erstes Ansprechen des Gleitschirms (die ersten 180°) en : keine unmittelbare Reaktion

en : keine unmittelbare Reaktion

Tendency to return to straight flight en : selbstständiges Ausleiten (G-Kraft abnehmend, Drehgeschwindigkeit abnehmend)

en : selbstständiges Ausleiten (G-Kraft abnehmend, Drehgeschwindigkeit abnehmend)

Turn angle to recover normal flight Less than 720°, spontaneous recovery

Less than 720°, spontaneous recovery

<u>Symmetric front collapse</u>	A	A
Entry Rocking back less than 45° Recovery Spontaneous in less than 3 s Dive forward angle on exit Dive forward 0° to 30° Change of course Entering a turn of less than 90° Cascade occurs No en : Faltleinen wurden benutzt no		Rocking back less than 45° Spontaneous in less than 3 s Dive forward 0° to 30° Entering a turn of less than 90° No no
<u>en : Symmetrischer Frontklapper mindestens 50% Flügeltiefe</u>	B	B
Entry Rocking back less than 45° Recovery Spontaneous in 3 s to 5 s Dive forward angle on exit Dive forward 0° to 30° Change of course Entering a turn of less than 90° Cascade occurs No en : Faltleinen wurden benutzt no		Rocking back less than 45° Spontaneous in 3 s to 5 s Dive forward 0° to 30° Entering a turn of less than 90° No no
<u>en : Symmetrischer Frontklapper im beschleunigten Flug mindestens 50% Flügeltiefe</u>	B	B
Entry Rocking back less than 45° Recovery Spontaneous in 3 s to 5 s Dive forward angle on exit Dive forward 30° to 60° Change of course Entering a turn of less than 90° Cascade occurs No en : Faltleinen wurden benutzt no		Rocking back less than 45° Spontaneous in 3 s to 5 s Dive forward 30° to 60° Entering a turn of less than 90° No no
<u>Exiting deep stall (parachutal stall)</u>	A	A
Deep stall achieved Yes Recovery Spontaneous in less than 3 s Dive forward angle on exit Dive forward 0° to 30° Change of course Changing course less than 45° Cascade occurs No		Yes Spontaneous in less than 3 s Dive forward 0° to 30° Changing course less than 45° No
<u>High angle of attack recovery</u>	A	A
Recovery Spontaneous in less than 3 s Cascade occurs No		Spontaneous in less than 3 s No
<u>Recovery from a developed full stall</u>	A	A
Dive forward angle on exit Dive forward 0° to 30° Collapse No collapse Cascade occurs (other than collapses) No Rocking back Less than 45° Line tension Most lines tight		Dive forward 0° to 30° No collapse No Less than 45° Most lines tight
<u>en : Kleiner einseitiger Klapper</u>	A	A
Change of course until re-inflation Less than 90° Maximum dive forward or roll angle Dive or roll angle 0° to 15° Re-inflation behaviour Spontaneous re-inflation Total change of course Less than 360° Collapse on the opposite side occurs en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung) Twist occurs No Cascade occurs No en : Faltleinen wurden benutzt no		Less than 90° Dive or roll angle 0° to 15° Spontaneous re-inflation Less than 360° en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung) No No no
<u>en : Großer einseitiger Klapper</u>	B	B
Change of course until re-inflation 90° to 180° Maximum dive forward or roll angle Dive or roll angle 15° to 45° Re-inflation behaviour Spontaneous re-inflation Total change of course Less than 360° Collapse on the opposite side occurs en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung) Twist occurs No Cascade occurs No en : Faltleinen wurden benutzt no		90° to 180° Dive or roll angle 15° to 45° Spontaneous re-inflation Less than 360° en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung) No No no
<u>en : Kleiner einseitiger Klapper im</u>	A	A

beschleunigten Flug		
Change of course until re-inflation	Less than 90°	Less than 90°
Maximum dive forward or roll angle	Dive or roll angle 15° to 45°	Dive or roll angle 15° to 45°
Re-inflation behaviour	Spontaneous re-inflation	Spontaneous re-inflation
Total change of course	Less than 360°	Less than 360°
Collapse on the opposite side occurs	en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)	en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)
Twist occurs	No	No
Cascade occurs	No	No
en : Faltleinen wurden benutzt	no	no
en : Großer einseitiger Klapper im beschleunigten Flug	B	B
Change of course until re-inflation	90° to 180°	90° to 180°
Maximum dive forward or roll angle	Dive or roll angle 15° to 45°	Dive or roll angle 15° to 45°
Re-inflation behaviour	Spontaneous re-inflation	Spontaneous re-inflation
Total change of course	Less than 360°	Less than 360°
Collapse on the opposite side occurs	en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)	en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)
Twist occurs	No	No
Cascade occurs	No	No
en : Faltleinen wurden benutzt	no	no
Directional control with a maintained asymmetric collapse	A	A
Able to keep course	Yes	Yes
180° turn away from the collapsed side possible in 10 s	Yes	Yes
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	More than 50 % of the symmetric control travel
Trim speed spin tendency	A	A
Spin occurs	No	No
Low speed spin tendency	A	A
Spin occurs	No	No
Recovery from a developed spin	A	A
Spin rotation angle after release	Stops spinning in less than 90°	Stops spinning in less than 90°
Cascade occurs	No	No
B-line stall	A	A
Change of course before release	Changing course less than 45°	Changing course less than 45°
Behaviour before release	Remains stable with straight span	Remains stable with straight span
Recovery	Spontaneous in less than 3 s	Spontaneous in less than 3 s
Dive forward angle on exit	Dive forward 0° to 30°	Dive forward 0° to 30°
Cascade occurs	No	No
Big ears	B	B
Entry procedure	Dedicated controls	Dedicated controls
Behaviour during big ears	Stable flight	Stable flight
Recovery	Spontaneous in 3 s to 5 s	Spontaneous in 3 s to 5 s
Dive forward angle on exit	Dive forward 0° to 30°	Dive forward 0° to 30°
Big ears in accelerated flight	A	A
Entry procedure	Dedicated controls	Dedicated controls
Behaviour during big ears	Stable flight	Stable flight
Recovery	Spontaneous in 3 s to 5 s	Spontaneous in 3 s to 5 s
Dive forward angle on exit	Dive forward 0° to 30°	Dive forward 0° to 30°
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	Stable flight
Alternative means of directional control	A	A
180° turn achievable in 20 s	Yes	Yes
Stall or spin occurs	No	No
Any other flight procedure and/or configuration described in the user's manual		
No other flight procedure or configuration described in the user's manual		