

**TEST REPORT DHV 03 MAC PARA VELVIA 28**
**Type** Mac Para Velvia 28

**Certificate-No** DHV GS-01-1562-06

**Holder of certificate** Skyline Flight Gear GmbH & Co. KG

**Manufacturer** MAC Para Technology Ltd

**Classification** 1-2 GH

**Winch tow** Yes

**Number of seats min / Number of seats max** 1 / 1

**Accelerator?** Yes

**Trimmers?** No

|   | BEHAVIOUR AT MIN WEIGHT IN FLIGHT(85 KG) | BEHAVIOUR AT MAX WEIGHT IN FLIGHT(110 KG) |
|---|--|---|
| <b>Take off</b>                               | <b>1-2</b>                               | <b>1-2</b>                                |
| <b>Inflation</b>                              | evenly, immediately                      | evenly, immediately                       |
| <b>Rising behaviour</b>                       | immediately comes over pilot             | immediately comes over pilot              |
| <b>Take off speed</b>                         | average                                  | average                                   |
| <b>Take off handling</b>                      | easy                                     | easy                                      |
| <b>Straight flight</b>                        | <b>1-2</b>                               | <b>1-2</b>                                |
| <b>Roll damping</b>                           | average                                  | average                                   |
| <b>Turn handling</b>                          | <b>1-2</b>                               | <b>1-2</b>                                |
| <b>Spin tendency</b>                          | slight                                   | slight                                    |
| <b>Control travel</b>                         | high                                     | high                                      |
| <b>Agility</b>                                | average                                  | average                                   |
| <b>Symmetric stall</b>                        | <b>1-2</b>                               | <b>1-2</b>                                |
| <b>Deep-stall limit</b>                       | average 60 cm - 75 cm                    | average 60 cm - 75 cm                     |
| <b>Full stall limit</b>                       | average 65 cm - 80 cm                    | average 65 cm - 80 cm                     |
| <b>Increase in steering power</b>             | high                                     | high                                      |
| <b>Front collapse</b>                         | <b>1-2</b>                               | <b>1-2</b>                                |
| <b>Pre-acceleration</b>                       | average                                  | average                                   |
| <b>Opening behaviour</b>                      | spontaneous, delayed                     | spontaneous, delayed                      |
| <b>Asymmetric collapse</b>                    | <b>1</b>                                 | <b>1</b>                                  |
| <b>Turn tendency</b>                          | < 90 degrees                             | < 90 degrees                              |
| <b>Change of course</b>                       | 90 - 180 degrees                         | 90 - 180 degrees                          |
| <b>Rate of turn</b>                           | average<br>with deceleration             | average<br>with deceleration              |
| <b>Max. roll/pitch angle</b>                  | less than 45 degrees                     | less than 45 degrees                      |
| <b>Loss of altitude</b>                       | average                                  | average                                   |
| <b>Stabilization</b>                          | spontaneous                              | spontaneous                               |
| <b>Opening behaviour</b>                      | spontaneous                              | spontaneous                               |
| <b>Countersteering an asymmetric collapse</b> | <b>1-2</b>                               | <b>1-2</b>                                |
| <b>Stabilization</b>                          | countersteering easy                     | countersteering easy                      |
| <b>Control travel</b>                         | average                                  | average                                   |
| <b>Control pressure increase</b>              | high                                     | high                                      |
| <b>Turn in opposite direction</b>             | easy, no tendency to stall               | easy, no tendency to stall                |
| <b>Opening behaviour</b>                      |  |   |
| <b>Full stall, symm. exit</b>                 | <b>1-2</b>                               | <b>1-2</b>                                |
| <b>Spin out of straight flight</b>            | <b>1-2</b>                               | <b>1-2</b>                                |
| <b>Spin out of turn</b>                       | <b>1-2</b>                               | <b>1-2</b>                                |
| <b>Spiral dive</b>                            | <b>1-2</b>                               | <b>1-2</b>                                |
| <b>Entry</b>                                  | easy                                     | easy                                      |
| <b>Spin tendency</b>                          | slight                                   | slight                                    |
| <b>Exit</b>                                   | turn continues through < 180 degrees     | turn continues through < 180 degrees      |
| <b>Sink rate after 720 °[m/s]</b>             | 9  | 12  |

|  |                      |                      |
|--|----------------------|----------------------|
| <b>B-line stall</b>                      | <b>1</b>             | <b>1</b>             |
| <b>Entry</b>                             | easy                 | easy                 |
| <b>Exit</b>                              | spontaneous          | spontaneous          |
| <b>Big ears</b>                          | <b>1</b>             | <b>1</b>             |
| <b>Entry</b>                             | easy                 | easy                 |
| <b>Recovery</b>                          | spontaneous, quickly | spontaneous, quickly |
| <b>Landing</b>                           | <b>1-2</b>           | <b>1-2</b>           |
| <b>Landing behaviour</b>                 | easy                 | easy                 |
| <b>Front collapse (accelerated)</b>      | <b>1-2</b>           | <b>1-2</b>           |
| <b>Pre-acceleration</b>                  | slight               | slight               |
| <b>Opening behaviour</b>                 | spontaneous, delayed | spontaneous, delayed |
| <b>Asymmetric collapse (accelerated)</b> | <b>1</b>             | <b>1</b>             |
| <b>Turn tendency</b>                     | < 90 degrees         | < 90 degrees         |
| <b>Change of course</b>                  | 90 - 180 degrees     | 90 - 180 degrees     |
| <b>Rate of turn</b>                      | average              | average              |
| <b>Max. roll/pitch angle</b>             | less than 45 degrees | less than 45 degrees |
| <b>Loss of altitude</b>                  | average              | average              |
| <b>Stabilization</b>                     | spontaneous          | spontaneous          |
| <b>Opening behaviour</b>                 | spontaneous          | spontaneous          |
| <b>Big ears accelerated</b>              | <b>1</b>             | <b>1</b>             |
| <b>Entry</b>                             | easy                 | easy                 |
| <b>Recovery</b>                          | spontaneous, quickly | spontaneous, quickly |
| <b>Supplementary remarks</b>             |                      |                      |