


Manufacturer		Type testing No.	EAPR-GS-7675/13
		Location	Monaco
Model	Yukon 19-X	Bad Grönenbach:	21.01.13



EAPR GmbH - Marktstr. 11 - D-87730 Bad Grönenbach - Germany

Date of testing	Minimum take off weight 27.12.12		Maximum take off weight 13.01.13	
Testpilot	Mike Küng		Hannes Tschofen	
Harness	EAPR-Testequipment		Academy Test Equipment	
Pilot's take off weight	70 kg		95 kg	

Classification	D
----------------	---



Test-criteria	Minimum take off weight	Evaluation	Maximum take off weight	Evaluation
<b>1. Inflation / take-off - 4.1.1</b>				
Rising behavior	Smooth, easy and constant rising	A	Smooth, easy and constant rising	A
Special take off technique required	No	A	No	A
<b>2. Landing - 4.1.2</b>				
Special landing technique required	No	A	No	A
<b>3. Speeds in straight flight - 4.1.3</b>				
Trim speed more than 30km/h	Yes	A	Yes	A
Speed range using the controls larger than 10km/h	Yes	A	Yes	A
Minimum speed	25 km/h to 30 km/h	B	25 km/h to 30 km/h	B
<b>4. Control movement - 4.1.4</b>				
Max. weight in flight up to 80kg	Increasing 40cm - 55cm	C		-
Max. weight in flight 80 to 100kg		-	Increasing 45cm - 60cm	C
Max. weight in flight greater than 100kg		-		-
<b>5. Pitch stability exiting accelerated flight - 4.1.5</b>				
Dive forward angle on exit	Dive forward less than 30°	A	Dive forward less than 30°	A
Collapse occurs	No	A	No	A
<b>6. Pitch stability operating controls during accelerated flight - 4.1.6</b>				
Collapse occurs	No	A	No	A
<b>7. Roll stability and damping - 4.1.7</b>				
Oscillations	Reducing	A	Reducing	A
<b>8. Stability in gentle spirals - 4.1.8</b>				
Tendency to return to straight flight	Spontaneous exit	A	Spontaneous exit	A
<b>9. Behaviour in a steeply banked turn - 4.1.9</b>				
Sink rate after two turns	More than 14m/s	B	More than 14m/s	B
<b>10. Symmetric front collapse - 4.1.10</b>				
Entry	Rocking back less than 45°	A	Rocking back less than 45°	A
Recovery	Spontaneous in 3 to 5 sec	B	Spontaneous in less than 3 sec	A
Dive forward angle on exit	30° - 60°	B	30° - 60°	B
Cascade occurs	Entering a turn of less than 90°	A	Keeping course	A
Entry	Rocking back greater than 45°	C	Rocking back greater than 45°	C
Recovery	Spontaneous in 3 to 5 sec	B	Spontaneous in 3 to 5 sec	B
Dive forward angle on exit	30° - 60°	B	30° - 60°	B
Cascade occurs	Entering a turn of less than 90°	A	Keeping course	A
<b>11. Exiting deep stall (parachutal stall) - 4.1.11</b>				

Deep stall achieved	Yes		Yes	
Recovery	Spontaneous in less than 3 sec	A	Spontaneous in less than 3 sec	A
Dive forward angle on exit	30° - 60°	B	30° - 60°	B
Change of course	Changing course less than 45°	A	Changing course less than 45°	A
Cascade occurs	No	A	No	A
<b>12. High angle of attack recovery - 4.1.12</b>				
Recovery	Spontaneous in less than 3 sec	A	Spontaneous in less than 3 sec	A
Cascade occurs	No	A	No	A
<b>13. Recovery from a developed full stall - 4.1.13</b>				
Dive forward angle on exit	60° - 90°	C	30° - 60°	B
Collapse	No collapse	A	No collapse	A
Cascade occurs (other than collapse)	No	A	No	A
Rocking backward	Less than 45°	A	Greater than 45°	C
Line tension	Most lines tight	A	Most lines tight	A
<b>14. Asymmetric collapse (trim speed) - 4.1.14</b>				
Change of course until re-inflation	90° - 180°	Dive or roll angle	15° - 45°	B
Re-inflation behavior	Spontaneous re-inflation		Spontaneous re-inflation	
Total change of course	Less than 360°		Less than 360°	
Collapse on the opposite side occurs	No		No	
Twist occurs	No		No	
Cascade occurs	No		No	
Change of course until re-inflation	90° - 180°	Dive or roll angle	45° - 60°	C
Re-inflation behavior	Spontaneous re-inflation		Spontaneous re-inflation	
Total change of course	Less than 360°		Less than 360°	
Collapse on the opposite side occurs	No		No	
Twist occurs	No		No	
Cascade occurs	No		No	
Change of course until re-inflation	90° - 180°	Dive or roll angle	45° - 60°	C
Re-inflation behavior	Spontaneous re-inflation		Spontaneous re-inflation	
Total change of course	Less than 360°		Less than 360°	
Collapse on the opposite side occurs	No		No	
Twist occurs	No		No	
Cascade occurs	No		No	
Change of course until re-inflation	90° - 180°	Dive or roll angle	45° - 60°	C
Re-inflation behavior	Spontaneous re-inflation		Spontaneous re-inflation	
Total change of course	Less than 360°		Less than 360°	
Collapse on the opposite side occurs	No		No	
Twist occurs	No		No	
Cascade occurs	No		No	
Change of course until re-inflation	90° - 180°	Dive or roll angle	60° - 90°	C
Re-inflation behavior	Spontaneous re-inflation		Spontaneous re-inflation	
Total change of course	Less than 360°		Greater than 360°	
Collapse on the opposite side occurs	No		No	
Twist occurs	No		No	
Cascade occurs	No		No	
<b>15. Directional control with a maintained asymmetric collapse - 4.1.15</b>				
Able to keep course straight	Yes	A	Yes	A
180° turn away from the collapsed side possible in 10 sec	Yes	A	Yes	A
Amount of control range between turn and stall or spin	25% to 50% of the symmetric control travel		25% to 50% of the symmetric control travel	
<b>16. Trim speed spin tendency - 4.1.16</b>				
Spin occurs	No	A	No	A
<b>17. Low speed spin tendency - 4.1.17</b>				
Spin occurs	No	A	No	A
<b>18. Recovery from a developed spin - 4.1.18</b>				
Spin rotation angle after release	Stops spinning in less than 90°	A	Stops spinning in 180° to 360°	D
Cascade occurs	No	A	No	A
<b>19. B-line-stall - 4.1.19</b>				
Change of course before release	Changing course less than 45°	A	Changing course less than 45°	A
Behaviour before release	Remains stable with straight span	A	Remains stable with straight span	A
Recovery	Spontaneous in less than 3 sec	A	Spontaneous in less than 3 sec	A
Dive forward angle on exit	30° - 60°	A	0° - 30°	A
Cascade occurs	No	A	No	A
<b>20. Big ears - 4.1.20</b>				
Entry procedure	Special device required	A	Standard technique	A
Behaviour during big ears	Stable flight	A	Stable flight	A
Recovery	Spontaneous in less than 3 sec	A	Spontaneous in less than 3 sec	A
Dive forward angle on exit	0° - 30°	A	0° bis 30°	A
<b>21. Big Ears in accelerated flight - 4.1.21</b>				
Entry procedure	Special device required	A	Standard technique	A
Behaviour during big ears	Stable flight	A	Stable flight	A
Recovery	Spontaneous in less than 3 sec	A	Spontaneous in less than 3 sec	A
Dive forward angle on exit	0° - 30°	A	0° bis 30°	A
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	A	Stable flight	A
<b>22. Behaviour exiting a steep spiral - 4.1.22</b>				

Tendency to return to straight flight	Spontaneous exit	A	Spontaneous exit	A
Turn angle to recover normal flight	720° to 1080°, spontaneous recovery	C	720° to 1080°, spontaneous recovery	C
<b>23. Alternative means of directional control - 4.1.23</b>				
180° turn achievable in 20 sec	Yes	A	Yes	A
Stall or spin occurs	No	A	No	A
<b>24. Any other flight procedure and/or configuration described in the user's manual - 4.1.24</b>				
Procedure works as described		NA		NA
Procedure suitable for novice pilots		NA		NA
Cascade occurs		NA		NA
<b>25. Remarks of testpilot:</b>				
Copyright Ralf Antz 2012	This Flight Test Report was generated automatically and is valid without signature			